



## BF 200 Up to 200 GPM

### Features

- Manifold connections are 3" 150 lb flanges
- Double bag filter
- Bag filter for high solids holding capacity
- Replaceable bag filters from 100 to 1 micron nominal rating
- No moving parts
- Skid mounted

### Technical

- Bag filter chambers connect in parallel
- Units are fitted with bleed valves and pressure gauges
- System can stand alone for sediment removal or be used in combination with filter equipment
- Footprint: 48" long x 36" wide x 66" high
- Dry weight: 800 lbs.



### Material Specifications

- Chambers constructed of 304 Stainless Steel
- Piping constructed of 304 stainless steel
- Each bag filter chamber holds one (1) 7" x 30" double- stitched filter bag
- Maximum operating pressure: 125psi
- Stainless Steel inlet and outlet manifolds

### Available Accessories

- Power Prime Pumps
- Spill Guard Containment berms
- Stainless Steel 304 and Carbon Steel storage tanks in
- Bi-Level, Mixer, Weir and Manifold configurations
- Polyethylene storage tanks
- Cartridge and bag filters
- HDPE pipe and fittings
- Roll off boxes, dewatering bins and vacuum boxes
- Flow meters and pressure reducing/ sustaining valves
- Aluminum Victaulic pipe and fittings
- Suction and discharge hose



### Rain for Rent

P.O. Box 2248  
Bakersfield CA 93303  
800-742-7246  
661-393-1542  
FAX 661-393-1542  
www.rainforrent.com  
info@rainforrent.com

Rain for Rent is a registered trademark  
of Western Oilfields Supply Company.  
Features and Specifications are subject to  
change without notice.