

Sand Media Filter

18-2SSK

Overview:

The 18-2SSK sand media filter features two media tanks for silica filtration media and provides a 3.5 square foot filtration area for flows up to 70 GPM.

Features:

- AC and DC powered automatic filter backwash controller that allows for timed, pressure differential or manual backwash intervals
- Fitted with air vents and pressure gauges
- Corrosion resistant
- Stainless steel inlet, outlet and backwash manifolds
- Pressure sustaining valve to aid in backwash operation
- Solar battery charger for DC operation in remote locations
- Filter tanks are constructed out of 304 stainless steel
- 4" media loading and removal ports
- Most effective backwash rate is 25 GPM min

Specs:

Max Flow	70 GPM
Material	Stainless Steel
Max PSI	100 PSI
Dry weight	700 lbs.
Footprint:	42" x 19"
Filtration Area:	3.5 square feet
Inlet x outlet	3" x 3" Victaulic



Accessories:

- Spillguard
- Stainless Steel 304 and Carbon Steel storage tanks in Bi-Level, Mixer, Weir and Manifold configurations
- Polyethylene storage tanks
- Cartridge and bag filters
- HDPE pipe and fittings
- Roll off boxes, dewatering bins and vacuum boxes
- Flow meters and pressure reducing/ sustaining valves
- Aluminum Victaulic pipe and fittings
- Suction and discharge hose



PUMPS • TANKS • FILTRATION • PIPE • SPILLGUARDS

Rain for Rent is a registered trademark of Western Oilfields Supply Company. Features and specifications are subject to change without notice.

Liquid Ingenuity®
800-742-7246
rainforrent.com