

# Sand Media Filter

24-3SSK

## Overview:

The 24-3SSK sand media filter features three media tanks for silica filtration media and provides a 9.4 square foot filtration area for flows up to 189 GPM.

## Features:

- 150 lbs. gravel and 400 lbs. sand per tank
- AC and DC powered automatic filter backwash controller that allows for timed, pressure differential or manual backwash intervals
- Fitted with air vents and pressure gauges
- Corrosion resistant
- Stainless steel inlet, outlet and backwash manifolds
- Pressure sustaining valve to aid in backwash operation
- Solar battery charger for DC operation in remote locations
- Filter tanks are constructed out of 304 stainless steel
- 6" media loading and removal ports
- Most effective backwash rate is 50 GPM min

## Specs:

|                  |                   |
|------------------|-------------------|
| Max Flow         | 189 GPM           |
| Material         | Stainless Steel   |
| Max PSI          | 100 PSI           |
| Dry weight       | 1400 lbs.         |
| Footprint:       | 78" x 22"         |
| Filtration Area: | 9.4 square feet   |
| Inlet x outlet   | 4" x 4" Victaulic |



## Accessories:

- Spillguard
- Stainless Steel 304 and Carbon Steel storage tanks in Bi-Level, Mixer, Weir and Manifold configurations
- Polyethylene storage tanks
- Cartridge and bag filters
- HDPE pipe and fittings
- Roll off boxes, dewatering bins and vacuum boxes
- Flow meters and pressure reducing/ sustaining valves
- Aluminum Victaulic pipe and fittings
- Suction and discharge hose



PUMPS • TANKS • FILTRATION • PIPE • SPILLGUARDS

Rain for Rent is a registered trademark of Western Oilfields Supply Company. Features and specifications are subject to change without notice.

**Liquid Ingenuity®**  
800-742-7246  
rainforrent.com