

# Sand Media Filter

36-2SSK

## Overview:

The 36-2SSK sand media filter features two media tanks for silica filtration media and provides a 14.2 square foot filtration area for flows up to 284 GPM.

## Features:

- 400 lbs. gravel and 800 lbs. sand per tank
- AC and DC powered automatic filter backwash controller that allows for timed, pressure differential or manual backwash intervals
- Fitted with air vents and pressure gauges
- Corrosion resistant
- Stainless steel inlet, outlet and backwash manifolds
- Pressure sustaining valve to aid in backwash operation
- Solar battery charger for DC operation in remote locations
- Filter tanks are constructed out of 304 stainless steel
- 8" media loading and removal ports
- Most effective backwash rate is 1.10 GPM min

## Specs:

Max Flow	284 GPM
Material	Stainless Steel
Max PSI	100 PSI
Dry weight	1300 lbs.
Footprint:	120" x 48"
Filtration Area:	14.2 square feet
Inlet x outlet	6" x 6" Victaulic



## Accessories:

- Spillguard
- Stainless Steel 304 and Carbon Steel storage tanks in Bi-Level, Mixer, Weir and Manifold configurations
- Polyethylene storage tanks
- Cartridge and bag filters
- HDPE pipe and fittings
- Roll off boxes, dewatering bins and vacuum boxes
- Flow meters and pressure reducing/ sustaining valves
- Aluminum Victaulic pipe and fittings
- Suction and discharge hose



PUMPS • TANKS • FILTRATION • PIPE • SPILLGUARDS

Rain for Rent is a registered trademark of Western Oilfields Supply Company. Features and specifications are subject to change without notice.

**Liquid Ingenuity®**  
800-742-7246  
rainforrent.com