

# Sand Media Filter

48-4SK

## Overview:

The 48-4SK sand media filter features four media tanks for silica filtration media and provides a 25 square foot filtration area for flows up to 1,000 GPM.

## Features:

- 500 lbs. gravel and 1,300 lbs. sand per tank
- AC and DC powered automatic filter backwash controller that allows for timed, pressure differential or manual backwash intervals
- Fitted with air vents and pressure gauges
- Corrosion resistant
- Carbon steel inlet, outlet and backwash manifolds
- Pressure sustaining valve to aid in backwash operation
- Solar battery charger for DC operation in remote locations
- 8" media loading and removal ports
- Most effective backwash rate is 190 GPM min



## Specs:

Max Flow	1,000 GPM
Material	Carbon Steel
Max PSI	80 PSI
Dry weight	4,500 lbs.
Footprint:	240" x 48"
Filtration Area:	50 square feet
Inlet x outlet	8" x 8" Victaulic

## Accessories:

- Spillguard
- Stainless Steel 304 and Carbon Steel storage tanks in Bi-Level, Mixer, Weir and Manifold configurations
- Polyethylene storage tanks
- Cartridge and bag filters
- HDPE pipe and fittings
- Roll off boxes, dewatering bins and vacuum boxes
- Flow meters and pressure reducing/ sustaining valves
- Aluminum Victaulic pipe and fittings
- Suction and discharge hose



PUMPS • TANKS • FILTRATION • PIPE • SPILLGUARDS

Rain for Rent is a registered trademark of Western Oilfields Supply Company. Features and specifications are subject to change without notice.

**Liquid Ingenuity®**  
800-742-7246  
rainforrent.com