Part of the WORKSAFE™ family of products

Overview:

Spillguards provide a safe and easy solution for secondary containment to help prevent costly incidents. Available in sizes from 6' to 50' with custom sizes available, the portable, lightweight, polyurethane Spillguards are puncture resistant and come with Rigid-Lock supports. The WORKSAFETM E-CONTAIN® Spillguard features safety improvements, space savings, ease and reduced clean-up costs. The E-CONTAIN® Spillguard is also lighter and easier to maintain, deploy and

Features:

- No inside or outside support straps, which decreases tripping hazards and strap damage from vehicle drive-over
- · One piece Spillguard, no assembly required
- · Smaller footprint
- · Easy to clean and repair damaged supports in the field
- Strong wind resistance
- Puncture resistant track belts and ground mats come standard with each Spillguard
- Patent pending design

Specs:

- Sizes from 6'x10'x8" to 48'x50'x1'
- Acid model (black) Spillguards approved for a temperature range of -10°F to 160°F
- Standard model (tan) Spillguards are approved for use in temperatures ranging from -50°F to 160°F
- Can be used in numerous applications to contain acids, caustics, hydrocarbons, fuels, fertilizers and many other hazardous materials
- Acid Spillguard models can be used in applications with Sulfuric acid, Sodium Hydroxide, Hydrochloric acid and Sodium Hypochlorite
- Spillguards require engineering review prior to use with Diesel, Gasoline, Crude oil and Mineral-based Hydraulic Fluid



Accessories:

- SolidGround® Traction Mat
- Spillguard Hose Bridge
- · Pipe & Hoses
- PipeStax[®]
- PipeStax® XL
- HoseTrax[™]
- · Puncture resistant track belts (Standard)
- Puncture resistant ground mats (Standard)

613000	3R	B
E-C 800 742 7 rainforrent	ONTAIN 7246 SPILLGUARD	

AVAILABLE SIZES		
LENGTH (FT)	WIDTH (FT)	WALL HEIGHT (IN)
6'	10'	8"
8'	14'	8"
10'	18'	8"
10'	30'	12"
10'	50'	12"
12'	16'	12"
28'	50'	12"
48'	50'	12"



Liquid Ingenuity 800-742-7246 rainforrent.com