

Hydronic Heater

E5000

Overview:

The E5000 hydronic heater is engineered for reliable performance and trouble-free starts. Digital temperature controller with push button adjustment allows operators to easily adjust Heat Transfer Fluid (HTF) output temperature for all concrete curing applications.

Features:

- Performance monitoring strobe light indicates that all systems are operating properly at a distance.
- 5,000 ft of hose for flexible, uncomplicated set up and operation for all applications.
- Three fuel options available: diesel, natural gas, propane.
- The E-5000 is easy to operate and dependable. It provides maximum flow and ensures consistent heat delivery for freeze protection, thawing, & curing applications.
- Safety features include: Electric Brakes, Ground fault receptacles, Main circuit breakers, Manual reset burner motor thermal protection, Electronic burner ignition, High temperature shutdown, No-flame shut down, Low fluid shutdown warning light, Vented closed loop circulation, Temperature gauges, Pressure gauges, Interior light.

Specs:

Powered	12kW Diesel Generator
18k Gallon Tanks heated	up to 12
Hose included	5,000 Feet
Dry weight	9,505 lbs.
Footprint	189" x 98" x 95"



Accessories:

- HX-Series Heat Xchangers
- 3004 Hose Handling Systems
- 4-Port Remote Manifolds
- Pump Packs
- Red Wave Heat Blankets

PUMPS • TANKS • FILTRATION • PIPE • SPILLGUARDS

THE SPECIFICATIONS CONTAINED IN THIS SHEET ARE OPERATING GUIDELINES AND ARE INTENDED TO BE GENERAL REPRESENTATIONS OF EQUIPMENT CAPABILITIES. ACTUAL PERFORMANCE WILL VARY BASED UPON SYSTEM APPLICATION, AGE OF EQUIPMENT, MANUFACTURER, AND OPERATION



Liquid Ingenuity
800-742-7246
rainforrent.com