

High Head Pump

HH80c

Overview:

The 4" suction x 3" discharge self-priming centrifugal HH80c high head pump provides up to a maximum of 450 gallons per minute pumping and up to 360 feet of head. This pump is usually mounted on a trailer and features the standard PowerPrime Clean Prime Venturi priming system which allows it to run continuously, unattended and even run dry.

Features:

- Suction lift to 28 feet
- Continuous self-priming
- Runs dry unattended
- 12-volt auto start electric control panel
- SAE-Mounted
- Flex coupled to diesel engine
- 24-hour capacity fuel tank
- Compressor/venturi automatic priming system
- Ductile iron volute with stainless steel impellers
- Replaceable wear plates

Specs:

Maximum Flow	450 GPM
Maximum Head	360 feet
Pump Size	4" x 3"
Maximum Solids Handling	1 inch
Dry weight	3,660 lbs.
Footprint: Trailer mounted model	135" x 66"
Fuel tank	120 gallon
Fuel consumption	2.3 gph @ 2,200 RPM



Accessories:

- Spillguard
- Suction and Discharge Hoses
- Fuel Nurse Tank
- VFD for electric driven models



PUMPS • TANKS • FILTRATION • PIPE • SPILLGUARDS

Rain for Rent is a registered trademark of Western Oilfields Supply Company. Features and specifications are subject to change without notice.

Liquid Ingenuity®
800-742-7246
rainforrent.com



Rain For Rent

CURVE: 01-0133-02-81

PUMP : HH-80C

ALL INFORMATION CONTAINED IN OR DISCLOSED BY THIS DOCUMENT IS CONSIDERED CONFIDENTIAL AND PROPRIETARY BY RAIN FOR RENT. ALL DISCLOSURES OF DESIGN INFORMATION AND REPRODUCTION OF THIS DOCUMENT AND ALL SALES RIGHTS ARE EXCLUSIVELY RESERVED BY AND TO RAIN FOR RENT AND OTHERS IS PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF RAIN FOR RENT

SUCTION	DISCHARGE	MAX. SPHERE	IMPELLER	IMPELLER	IMPELLER & WEAR RINGS
4"	3"	0.41"	7 VANE	14"	BRASS

