

# Oil Water Separator

OWS200

## Overview:

The OWS200 is a parallel corrugated plate gravity displacement type separator designed in accordance with API 421 to remove free and dispersed non emulsified oil and settleable solids. It is skid mounted with leveling jacks. It requires no power and features no moving parts for ease and reliability.

## Features:

The OWS200 removes free and dispersed non-emulsified oil, settleable solids and additionally functions as a gravity flow oil-skimmer for flows up to 200 GPM.

- 5 cubic feet sludge capacity
- 0.5 inch coalescing pack or oil attracting media
- One tank requiring 12 coalescing packs



## Specs:

Flow	Up to 200 GPM
Material	Stainless Steel
Dry weight	2700 lbs.
Footprint:	102" x 82"
Inlet x outlet	6" x 6" Flange

## Accessories:

- E-CONTAIN® Spillguards
- SolidGround® Traction Mats
- Pumps
- Tanks
- PipeStax®
- HoseTrax™
- Suction and Discharge Hoses



PUMPS • TANKS • FILTRATION • PIPE • SPILLGUARDS

Rain for Rent is a registered trademark of Western Oilfields Supply Company. Features and specifications are subject to change without notice.

**Liquid Ingenuity®**  
800-742-7246  
rainforrent.com