

Aluminum Pipe

Latch Style

Overview:

Latch Style Mainline Aluminum Pipe is light weight, easy to move, and simple to connect. This pipe is often used for irrigation mainlines, water transfer lines, construction and effluent transfer needs. Purchased pipe can be embossed with custom name to fit your identification needs. Available with heavy ends or rolled ends for your pipe needs.

Features:

- Pipe constructed with 3004-H26 alloy
- Each joint pressure tested to 225 psi
- Aluminum A-356 welded couplers feature a welded latch pad with positive alignment.
Aluminum coupler sizes: 4", 5", 6", 8", 10"
- Steel roll-formed AK carbon steel couplers with hot dipped galvanized finish are pressed into tubing with a Nupon epoxy adhesive. They feature band and latch positive alignment.
Steel coupler sizes: 2", 3", 4", 5", 6", 8"



Pipe Specs:

Diameter	Wall Thickness	Pipe weight (lbs/ft)	Maximum Working PSI
2"	.050	0.369	80
3"	.050	0.554	80
4"	.050	0.738	80
5"	.051	0.942	80
6"	.058	1.280	80
8"	.064	1.890	80
10"	.064	2.360	80



PUMPS • TANKS • FILTRATION • PIPE • SPILLGUARDS

Rain for Rent is a registered trademark of Western Oilfields Supply Company. Features and specifications are subject to change without notice.

Liquid Ingenuity®
800-742-7246
rainforrent.com