

Aluminum Pipe

Ringlock Style Mainline

Overview:

Ringlock Style Mainline Aluminum Pipe is light weight, easy to move, and simple to connect. This pipe is often used for irrigation mainlines, water transfer lines, construction and effluent transfer needs. Available for both rental and purchase, your pipe order can be custom embossed to your naming preference.

Features:

- Pipe constructed with 3004-H26 alloy
- Each joint pressure tested to 225 psi
- Aluminum A-356 welded couplers
Aluminum coupler sizes: 6", 8", 10"
- Steel roll-formed AK carbon steel couplers with hot dipped galvanized finish pressed into tubing with a Nupon epoxy adhesive
Steel coupler sizes 4", 5", 6", 8", 10", 12"



Pipe Specs:

Diameter	Wall Thickness	Pipe weight (lbs/ft)	Maximum Working PSI
4"	.050	0.738	80
5"	.051	0.942	80
6"	.058	1.280	80
8"	.064	1.890	80
10"	.064	2.360	80
12"	.064	2.830	80



PUMPS • TANKS • FILTRATION • PIPE • SPILLGUARDS

Rain for Rent is a registered trademark of Western Oilfields Supply Company. Features and specifications are subject to change without notice.

Liquid Ingenuity
800-742-7246
rainforrent.com